

Features of Each Press Series

SERIES	MODEL NO.	PRESS-ING METHOD	DRIVE POSI-TION	PRESS-ING MOTION	DEPTH OF FILL	COMPACT-ING SPEED	FEATURES		
S-EX	S-500EX S-200EX	DIE EJECTION POSITION CONSTANT	UPPER SECTION	CRANK	150mm	5 ~ 20 spm	<ul style="list-style-type: none"> * FOR HIGH PRECISE, HIGH DENSITY, COMPLCATED PM PARTS, ETC. * DIESET FOR UPPER-3/LOWER-3 STAGE PRESSING WITH CORE STOP MECHANISM IS POSSIBLE. * QUICK DIESET (DIE ADAPTOR) CHANGER. * SERVO DRIVE FEEDER CUP IS ADOPTED. * OIL BATH LUBRICATION IS ADOPED AND EASY MAINTENANCE.. 		
	S-400EX					4 ~ 16 spm			
S-N S-Long	S-10A		PRESSING POSITION CONSTANT	LOWER SECTION	TOGGLE	80mm	5 ~ 20 spm	<ul style="list-style-type: none"> * STANDARD MODEL WITH ALL ROUND PERFORMANCE. * FOR VARIOUS TYPE OF COMPONENTS BY THE DIESET CHANG OVER METHOD. * STABLE PRESSING BY ORIGINALLY DEVELOPED DIESET CONTRL DEVICE. * EASY OPERATION. * TOGGLE LINK DRIVE SYSTEM SUITABLE FOR POOR FLOWABILI TY POWDER. 	
	S-20A					100mm			
	S-40N,S-60N, S-60					120mm			
	S-100N					120mm			
	S-200					130mm			
S-	S-6				60mm	5 ~ 20 spm	60mm	5 ~ 20 spm	<ul style="list-style-type: none"> * SUITABLE FOR COMPERATIVELY SIMPLD SHAPED PARTS. * INEXPENSIVE TYPE OF MODELS. * VARIOUS COMPONENTS BY THE DIESET CHAGEOVER METHOD. * STABLE PRESSING BY TOGGLE LINK DRIVE MECHANISM.
	S-15,S-20								
IE-	IE-10,IE-20				DIE EJECTION POSITION CONSTANT	LOWER SECTION	CRANK	40mm	15 ~ 60 spm
	IE-40,IE-60	60mm						12 ~ 48 spm	
T-HS-	T-HS-3	30mm					25 ~ 100 spm	CRANK NON CIRCULAR GEAR	30mm
	T-HS-4		60mm						
	T-HS-10B		20 ~ 80 spm						
	T-HS-40								
T-HS-N	T-HS-10N	20mm	25 ~ 100 spm	<ul style="list-style-type: none"> * SPECIALLY DEVELOPED FOR PRODUCTION OF THIN PARTS. * DIESET BUILT-IN TYPE, 2-STAGE PRESSING. * OIL BATH LUBRICATION METHOD AND EASY MAINTENANCE. 					
	T-HS-20N	25mm	20 ~ 80 spm						
SX-	SX-10	DIE EJECTION POSITION CONSTANT	UPPER SECTION	CRANK			80mm	max. 25 spm	<ul style="list-style-type: none"> * UPPER/LOWER RAM MOVEMENT BY SERVO MOTOR, 30%. * MULTIPLE STAGE DIESET OPERATED BY HYDRAULIC SERVO. * DESIGN OF SOFTWARE TO SUITE FOR NEEDS BY CUSTOMER. * PRECISE SETTING FOR MOVEMENT AND HIGH REPETITION ACCURACY. * PERSONAL COMPUTER IS BUILT IN AND EASY OPERATION AND EASY MAINTENANCE FOR DATA.
	SX-20						100mm		
	SX-40				100mm				
	SX-50				120mm				
SX-S	SX-10S		LOWER SECT.	60mm	max. 25 spm	<ul style="list-style-type: none"> * INEXPENSIVE MODEL IN COMPARISON WITH SX-SERIES. * EASY SETTING OF UPPER-1/LOWER-1 STGE PRESSING. 			